IN THE CLAIMS

1. (Three Times Amended) A method for [establishing cryptographic] communications of a message cryptographically processed with RSA (Rivest, Shamir & Adleman) public key encryption, comprising the [step] steps of:

developing k distinct random prime numbers $p_1, p_2, ..., p_k$, wherein k is an integer greater than 2;

providing a number e relatively prime to $(p_1-1)\cdot (p_2-1)\cdot \dots \cdot (p_k-1)$;

providing a composite number n equaling the product $p_1 \cdot p_2 \cdot ... \cdot p_k$;

receiving a ciphertext word signal C which is formed by encoding a plaintext message word signal M to a ciphertext word signal C, where M corresponds to a number representative of [a] the message and

 $0 \le M \le n-1$,

[n being a composite number formed from the product of $p_1 \cdot p_2 \dots \cdot p_k$ where k is an integer greater than 2, p_1 , p_2 , ... p_k are distinct prime numbers, and] where C is a number representative of an encoded form of the plaintext message word signal M such that $C \equiv M^e \pmod{n}$, and where e is associated with an intended recipient of the ciphertext word signal C; and [, wherein said encoding step comprises the step of: transforming said message word signal M to said ciphertext word signal C whereby $C = M^e \pmod{n}$

where e is a number relatively prime to $(p_1 - 1) \cdot (p_2 - 1)$

deciphering the received ciphertext word signal C at the intended recipient having available to it the k distinct random prime number $p_1, p_2, \dots p_k$:

wherein p and q are a pair of prime numbers that product of which equals n, and

wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

2. (Twice Amended)The method according to claim 1, [comprising the further step of:] wherein the deciphering step includes

establishing a number, d, as a multiplicative inverse of e(mod(lcm($(p_1 - 1), (p_2 - 1), ..., (p_k - 1)))$), and

decoding the ciphertext word signal C to the <u>plaintext</u> message word signal M[, wherein said decoding step comprises the step of: transforming said ciphertext word signal C] where[by:] $[M=C^d \pmod{n}]$ $\underline{M}=C^d \pmod{n}$.

[where d is a multiplicative inverse of $e(mod(lcm((p_1-1), (p_2-1), ..., (p_k-1)))).]$

3. (Three Times Amended) A method for [transferring a message signal M_i in a] communications of a message signal M_i cryptographically processed with RSA public key encryption in a system having j terminals, [wherein] each terminal [is] being characterized by an encoding key $E_i = (e_i, n_i)$ and a decoding key $D_i = (d_i, n_i)$, where i = 1, 2, ..., j, and [wherein] the message signal M_i corresponds to a number representative of a message-to-be-received [transmitted] from the i^{th} terminal, the method comprising the steps of: establishing n_i where n_i is a composite number of the form

 $[n_i = P_{i,1} \cdot p_{i,2} \cdot, \dots, p_{i,k}] \underline{n_i} = \underline{p_{i,1}} \cdot \underline{p_{i,2}} \cdot, \dots, p_{i,k}$ where k is an integer greater than 2,

 $p_{i,1}, p_{i,2}, \ldots, p_{i,k}$ are distinct <u>random</u> prime numbers,

 e_i is relatively prime to $[lcm(p_{i,1} -1, p_{1,2} -1, p_{i,k} -1)] \underline{lcm(p_{i,1} -1, p_{i,2} -1, \dots p_{i,k} -1)}$, and

 d_i is selected from the group consisting of the class of numbers equivalent to a multiplicative inverse of

 $e_i \pmod{(lcm((p_{i,1}-1), (p_{i,2}-1), \dots, (p_{i,k}-1)))}$, comprising the step of:]

receiving by a recipient terminal (i = y) from a sender terminal ($i = x, x \neq y$) a

ciphertext signal C_X formed by encoding a digital message word signal M_X , wherein the encoding includes $[M_A$ for transmission from a first terminal (i=A) to a second terminal (i=B), said encoding step including the sub-step of:]

- transforming said message word signal M_A to one or more message block word signals $[M_A"]$ $\underline{M}_X"$, each block word signal $[M_A"]$ $\underline{M}_X"$ corresponding to a number representative of a portion of said message word sign $[M_A]$ \underline{M}_X in the range $0 \le M_X" \le n_y 1$ $[0 \le M_A" \le n_B 1]$, and
- transforming each of said message block word signals $[M_A"]$ $\underline{M}_X"$ to a ciphertext word signal $[C_A, C_A]$ corresponding] \underline{C}_X that corresponds to a number representative of an encoded form of said message block word signal $[M_A"]$ $\underline{M}_X"$ [,] where [by:] $[C_A \equiv M_A "^{eB} \pmod{n_B}]$ $\underline{C}_X \equiv \underline{M}_X"^{ey} \pmod{n_y}$; and
- deciphering the received ciphertext word signal C_x at the recipient terminal having available to it the k distinct random prime numbers $p_{y,1}, p_{y,2}, \ldots, p_{y,k}$ for establishing its d_y ;

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

4. (Five Times Amended) A [cryptographic communications] system for communications of a message cryptographically processed with an RSA public key encryption, comprising: a communication [medium] channel for transmitting a ciphertext word signal C; [an] encoding means coupled to said channel and adapted for transforming a transmit message

word signal M to [a] the ciphertext word signal C using a composite number, n, where n is a product of the form

 $\underline{n} = \underline{p}_1, \underline{p}_2, \dots \underline{p}_k$

k is an integer greater than 2, and

 $p_1, p_2, \dots p_k$ are distinct random prime numbers [and for transmitting C on said channel], where the transmit message word signal M corresponds to a number representative of [a] the message and

 $0 \leq M \leq \text{n-1}$ [where n is a composite number of the form

$$n=p_1\cdot p_2\cdot ...\cdot p_k$$

where k is an integer greater than 2 and p₁, p₂,...,p_k are distinct prime numbers, and] where the ciphertext word signal C corresponds to a number representative of an [enciphered] encoded form of said message through a relationship of the form [and corresponds to]

 $C \equiv M^e \pmod{n}$, and

where e is a number relatively prime to $lcm(p_1 - 1, p_2 - 1, ..., p_k - 1)$; and

[a] decoding means coupled to said channel and adapted for receiving the ciphertext word signal C from said channel and, having available to it the k distinct random prime numbers p₁, p₂,...p_k, for transforming the ciphertext word signal C to a receive message word signal M' where M' corresponds to a number representative of a [deciphered] decoded form of the ciphertext word signal C [and corresponds to] through a relationship of the form M'≡C_d (mod n) where d is selected from the group consisting of [the] a class of numbers equivalent to

where d is selected from the group consisting of [the] \underline{a} class of numbers equivalent to a multiplicative inverse of

$$e(mod(lcm((p_1 -1), (p_2 -1), ..., (p_k -1))));$$

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

- 5. (Three Times Amended) A [cryptographic communications] system for communications of a message cryptographically processed with an RSA public key encryption, the system having a plurality of terminals coupled by a communications channel, [including] comprising:
- a first terminal of the plurality of terminals characterized by an [associated] encoding key $E_A = (e_A, n_A)$ and a decoding key $D_A = (d_A, n_A)$,

Where[in] n_A is a composite number of the form

 $n_A = p_{A,1} \cdot p_{A,2} \cdot \ldots \cdot p_{A,k}$

where

k is an integer greater than 2,

 $p_{A,1}, p_{A,2}, \ldots, p_{A,k}$ are distinct <u>random</u> prime numbers,

e_A is relatively prime to

$$lcm(p_{A,1}-1, p_{A,2}-1, \ldots, p_{A,k}-1), and$$

 d_A is selected from the group consisting of the class of numbers equivalent to a multiplicative inverse of

$$e_A \pmod{(lcm((p_{A,1}-1), (p_{A,2}-1), \dots, (p_{A,k}-1)))}; and[,]$$

[and including] a second terminal of the plurality of terminals having[, comprising:]

blocking means for transforming a <u>first</u> message, [-to-be-transmitted] <u>which is to be</u>

<u>transmitted on said communications channel</u> from said second terminal to said

first terminal, <u>into</u> one or more transmit message word signals M_B , where <u>each</u> M_B corresponds to a number representative of said <u>first</u> message in the range $0 \le M_B \le n_A - 1$,

encoding means coupled to said channel and adapted for transforming each transmit message word signal M_B to a ciphertext word signal C_B that [and for transmitting C_B on said channel, where C_B] corresponds to a number representative of an [enciphered] encoded form of said first message [and corresponds to] through a relationship of the form

$$[C_B \equiv M_B^{eA} \pmod{n_A}] \underline{C_B} \equiv M_B^{eA} \pmod{n_A},$$

[wherein] said first terminal <u>having</u> [comprises:]

decoding means coupled to said channel and adapted for receiving <u>each of</u> said ciphertext word signals C_B from said channel and, <u>having available to it the k</u> distinct

random prime numbers $p_{A,1}$, $p_{A,2}$, ... $p_{A,k}$, for transforming each of said ciphertext word signals C_B to a receive message word signal $[M_B]$ M'_B , and

means for transforming said receive message word signal[s] [M'] M'_B to said first message, where [M'] M'_B [is] corresponds to a number representative of a [deciphered] decoded form of C_B [and corresponds to] through a relationship of the form

$$[M'_B \equiv C_B^{dA} \pmod{n_A}] \underline{M'_B} \equiv C_B^{dA} \pmod{n_A};$$

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

6. (Twice Amended) The system according to claim 5 wherein said second terminal is characterized by an [associated] encoding key $[E_B = (e_B, n_B)] E_B = (e_B, n_B)$ and \underline{a} decoding key $[DB = (D_B, d_B)] D_B = (d_B, n_B)$, where [:]

n_B is a composite number of the form

$$n_B = p_{B,1} \ [\cdot] p_{B,2} \cdot \ldots \cdot p_{B,k}$$

where k is an integer greater than 2,

 $\underline{p_{B,1}}, \underline{p_{B,2}}, \ldots, \underline{p_{B,k}}$ $[P_{B,1}, P_{B,2}, \ldots, P_{B,k}]$ are distinct prime numbers,

e_B is relatively prime to

$$lcm(p_{B,1}-1, p_{B,2}-1, ..., p_{B,k}-1), and$$

 d_B is selected from the group consisting of [the] \underline{a} class of numbers equivalent to a multiplicative inverse of

$$e_B \pmod{(lcm((p_{B,1}-1), (p_{B,2}-1), \ldots, (p_{B,k}-1)))},$$

[wherein] said first terminal [comprises:] further having

blocking means for transforming a <u>second</u> message, [to-be-transmitted] <u>which is to be</u>

<u>transmitted on said communications channel</u> from said first terminal to said

second terminal, to one or more transmit message word signals M_A, where

each M_A corresponds to a number representative of said message in the range

$$[0 \le M_A^{eB} \pmod{n_B}] \underbrace{0 \le M_A \le n_B-1}$$

encoding means coupled to said channel and adapted for transforming each transmit message word signal M_A to a ciphertext word signal C_A and for transmitting C_A on said channel, [

] where C_A corresponds to a number representative of an <u>encoded</u> [enciphered] form of said <u>second</u> message [and corresponds to] <u>through a relationship of the form</u>

$$[C_A \equiv M_A^{eB} \pmod{n_B}] \subseteq \underline{C_A} \equiv M_A^{eB} \pmod{n_B}$$

[wherein] said second terminal [comprises;] further having

decoding means coupled to said channel and adapted for receiving <u>each of said</u>
ciphertext word signals C_A from said channel and, <u>having available to it the k</u>
distinct

random prime numbers $p_{B,1}$, $p_{B,2}$, ... $p_{B,k}$, for transforming each of said ciphertext word signals to a receive message word signal $[M_A']$ $\underline{M'_A}$, and means for transforming said receive message word signals $[M_A]$ $\underline{M'_A}$ to said second message, [] where [M'] $\underline{M'_A}$ corresponds to a number representative of a [deciphered] decoded form of C_A [and corresponds to] through a relationship of the form $[M_A'] \equiv C_A^{dB}$ (mod n_B)] $\underline{M'_A} \equiv C_A^{dB}$ (mod n_B).

- 7. Cancel claim 7.
- 8. Cancel claim 8.

- 9. (Three Times Amended) A [communication] system for [transferring] communications of message signals [M_i] cryptographically processed with RSA public key encryption, comprising:
- j terminals including first and second terminals [stations], each of the j [stations] terminals being characterized by an encoding key E_i =(e_i , n_i) and decoding key D_i =(d_i , n_i)[], where i=1,2,...,j, [and wherein

 M_i corresponds to a number representative of a message signal to be transmitted from the ith terminal,] each of the j terminals being adapted to transmit a particular one of the message signals where an ith message signal M_i is transmitted from an ith terminal and

 $0 \leq M_i \leq n_i - 1$,

n_i [is] being a composite number of the form

$$[\mathbf{n}_i = \mathbf{p}i_{i,1} \cdot \mathbf{p}_{i,2} \cdot \ldots \cdot \mathbf{p}_{i,k}] \underline{\mathbf{n}_i = \mathbf{p}i_{i,1} \cdot \mathbf{p}_{i,2} \cdot \ldots \cdot \mathbf{p}_{i,k}}$$

where

k is an integer greater than 2,

 $p_i, 1, \, p_{i,2}, \, \ldots, \, p_{i,k}$ are distinct \underline{random} prime numbers,

e_i is relatively prime to

$$lcm(p_{i,1}-1,p_{i,2}-1,\ldots,p_{i,k}-1), \underline{and}$$

 d_i is selected from the group consisting of the class of numbers equivalent to a multiplicative inverse of

 $e_i \pmod{(lcm((p_{i,1}-1), (p_{i,2}-1), \ldots, (p_{i,k}-1)))};$

said [a] first terminal [one of the j terminals] including

means for encoding a digital message word signal $[M_A]$ M_1 [for transmission] to be transmitted from said first terminal (i=1[A]) to [a] said second terminal [one of the j terminals] (i=2[B]), said encoding means [for]

transforming said <u>digital</u> message word signal $[M_A]$ M_1 to a signed message word signal $[M_{As}]$ M_{1s} using a relationship of the form $[M_{1s}]$ corresponding to a number representative of an encoded form of said message word signal M_A ,

whereby:]

$$[M_{AS} \equiv M_A^{dA} \pmod{n_A}] \underline{M_{1s}} \equiv M_1^{d1} \pmod{n_1}$$
; and

means for transmitting said signed message word signal M_{1s} from said first terminal to said second terminal, wherein said second terminal includes means for decoding said message word signal M_{1s} to said digital message word signal M_{1s}

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

10. (Twice Amended) The system of claim 9 [further comprising: means for transmitting said signal message word signal M_{As} from said first terminal to said second terminal, and wherein said second terminal includes means for decoding said signed message word signal M_{As} to said digital message word signal M_A, said second terminal including: means for] wherein the decoding signed message word signal M_{As} includes means for transforming from said signed message word signal M_{As} [, whereby] using a

$$[M_A \equiv M_{As}^{eA} \pmod{n_A}] \underline{M_1 \equiv M_{1s}^{e1} \pmod{n_1}}.$$

relationship of the form

- 11. (Four Times Amended) A communications system for transferring a message signal [M_i] <u>cryptographically processed with RSA public key encryption</u>, the communications system comprising:
- j communication stations <u>including first and second stations</u>, each <u>of the j communication</u>

 <u>stations being characterized by an encoding key E_i=(e_i, n_i) and <u>a decoding key D_i =(d_i, n_i)</u>, where i=1, 2, ..., j, [and wherein M_i corresponds to a number representative of a message signal to be transmitted from the ith terminal,] <u>each of the j communication</u>

 <u>stations being adapted to transmit a particular one of the message signals where an ith message signal M_i is received from an ith communication station, and</u></u>

 $0 \le M_i \le n_1 - 1$

n_i [is] being a composite number of the form

$$n_i = p_i, 1 \cdot p_{i,2} \cdot \ldots \cdot p_{i,k}$$

where

k is an integer greater than 2,

 $p_{i,1}, p_{i,2}, \ldots, p_{i,k}$ are distinct <u>random</u> prime numbers,

 e_i is relatively prime to $lcm(p_{i,1}-1,p_{i,2}-1,\ldots,p_{i,k}-1)$, and

 d_i is selected from the group consisting of the class of numbers equivalent to a multiplicative inverse of

 $e_i \pmod{(cm((p_{i,1}-1), (p_{i,2}-1), \ldots, (p_{i,k}-1)))}$

said first station [one of the j communication stations] including

means for encoding a digital message word signal $[M_A]$ $\underline{M_1}$ [for transmission] to be transmitted from said first station [one of the j communication stations] (i=1[A]) to [a] said second station [one of the j communication stations] (i=2[B]),

means for transforming said <u>digital</u> message word signal $[M_A]$ \underline{M}_1 to one or more message block word signals $[M_A$ '] \underline{M}_1 ", each block word signal $[M_A$ '] \underline{M}_1 " being a number representative of a portion of said message word signal $[M_A$ '] \underline{M}_1 in the range

 $0 \le M_1'' \le n_2 - 1$ [$0 \le M_A \le n_B - 1$], and

means for transforming each of said message block word signals $\underline{M_1}$ " M_A] to a ciphertext word signal $\underline{C1}$ using a relationship of the form $[C_A, C_A]$ corresponding to a number representative of an encoded form of said message block word signal M_A ", whereby:]

 $[C_A \equiv M_A \underline{"}^{Eb} \pmod{n_B}] \underline{C_1} \equiv M\underline{"_1}^{e2} \pmod{n_2}$; and

means for transmitting said ciphertext signals C₁ from said first station to said second station, wherein said second station includes

means for deciphering said ciphertext signals C_1 using $p_{2,1}, p_{2,2}, \dots p_{2,k}$ to produce said message word signal M_1 ;

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

12. (Twice Amended) The <u>communications</u> system of claim 11, [further comprising: means for transmitting said ciphertext word signals from said first terminal to said second terminal, and] wherein [said second terminal] <u>the deciphering means</u> includes means for decoding said ciphertext word signals <u>C1</u> to said message <u>block</u> word signals [MA] <u>M1" using a relationship of the form</u> [, said second terminal including:

means for transforming each of said ciphertext word signals C_A to one of said message block word signals M_A ", whereby

$$M_A \equiv C_A^{Db} \pmod{n_B} M_1 \equiv C_1^{d2} \pmod{n_2}$$
, and

means for transforming said message block word signals $[M_A"]\underline{M_1}$ " to said message word signal $[M_A]\underline{M_1}$.

13. Cancel claim 13.

14. (Previously Presented) A method of communicating a message cryptographically processed with an RSA public key encryption, comprising the steps of:

selecting a public key portion e associated with a recipient intended for receiving the message;

developing k distinct random prime numbers, $p_1, p_2, \dots p_k$, where $k \ge 3$, and checking that each of the k_i distinct random prime numbers minus $1, p_1-1, p_2-1, \dots p_k-1$, is relatively prime to the public key portion e;

computing a composite number, n, as a product of the at least three distinct random prime numbers;

receiving a ciphertext message formed by encoding a plaintext message data M to the ciphertext message data C using a relationship of the form C≡M^e (mod n), where M represents the message, where 0≤M≤n-1 and where the sender knows n and the public key portion e but has no access to the k distinct random prime numbers, p₁, p₂, ... p_k; and

deciphering at the recipient the received ciphertext message data C to produce the message, the recipient having access to the k distinct random prime numbers,

 $p_1, p_2, \dots p_k$;

wherein p and q are a pair of prime numbers that product of which equals n, and

wherein developing the at least three distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

- 15. (Previously Presented) The method according to claim 14, comprising the further step of:
- establishing a private key portion d by a relationship to the public key portion e in the form of $\underline{d} \equiv e^{-1}(\text{mod}((p_1 1) \cdot (p_2 1) \cdots (p_k 1))),$

wherein the deciphering step includes decoding the ciphertext message data C to the plaintext message data M using a relationship of the form $M \equiv C^d \pmod{n}$.

- 16. (Previously Presented) A method of communicating a message cryptographically processed with RSA public key encryption, comprising the steps of: selecting a public key portion e;
- developing k distinct random prime numbers, $p_1, p_2, \dots p_k$, where $k \ge 3$, and checking that each of the k distinct random prime numbers minus $1, p_1-1, p_2-1, \dots p_k-1$, is relatively prime to the public key portion e;
- establishing a private key portion d by a relationship to the public key portion e in the form of $\underline{d} \equiv e^{-1} \pmod{(p_1-1)\cdot(p_2-1)\cdots(p_k-1)};$
- computing a composite number, n, as a product of the k distinct random prime numbers;

 receiving a ciphertext message data C representing an encoded form of a plaintext message

 data M; and
 - decoding the received ciphertext message data C to the plaintext message data M

 using a relationship of the form M≡C^d (mod n), the decoding performed by a

 recipient owning the private key portion d and having access to the k distinct

 random prime numbers, p₁, p₂, ... p_k:

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

- 17. (Previously Presented) The method according to claim 16, wherein the ciphertext message data C is formed by encoding the plaintext message data M to the ciphertext message data C using a relationship of the form $C \equiv M^e \pmod{n}$, wherein $0 \leq M \leq n-1$ and wherein n and the public key portion e are accessible to the sender although it has no access to the k distinct random prime numbers, $p_1, p_2, \dots p_k$.
- 18. (Previously Presented) A method of communicating a message cryptographically processed with RSA public key encryption, comprising the steps of: selecting a public key portion e;
- developing k distinct random prime numbers, $p_1, p_2, \dots p_k$, where $k \ge 3$, and checking that each of the k distinct random prime numbers minus $1, p_1-1, p_2-1, \dots p_k-1$, is relatively prime to the public key portion e;
- establishing a private key portion d by a relationship to the public key portion e of the form d $\equiv e^{-1} \pmod{(p_1 1) \cdot (p_2 1) \cdots (p_k 1)};$

computing a composite number, n, as a product of the k distinct random prime numbers;
encoding a plaintext message data M with the private key portion d to produce a signed
message M_s using a relationship of the form M_s≡M^d (mod n), where 0≤M≤n-1
receiving the signed message M_s; and

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

deciphering the signed message to produce the plaintext message data M;

- 19. (Previously Presented) The method of claim 18, wherein the deciphering step includes:
- decoding the signed message M_s with the public key portion e to produce the plaintext message data M using a relationship of the form $M \equiv M_s^e \pmod{n}$.
- 20. (Previously Presented) A method for communicating a message cryptographically processed with RSA public key encryption, comprising the steps of:

 sending to a recipient a cryptographically processed message formed by assigning a number

 M to represent the message in plaintext message form, and

cryptographically transforming the assigned number M from the plaintext message form to a number C that represents the message in an encoded form, wherein the number C is a function of

the assigned number M,

a number n that is a composite number equaling the product of at least three distinct random prime numbers, wherein 0 < M < n-1, and

an exponent e that is a number relatively prime to a lowest common multiplier of the at least three distinct random prime numbers,

wherein the number n and exponent e having been obtained by the sender are associated with the recipient to which the message is intended; and

receiving the cryptographically processed message which is decipherable by the recipient based on

the number n,

another exponent d, and

the number C,

wherein the exponent d is a function of the exponent e and the at least three distinct random prime numbers;

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the at least three distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

- 21. (Previously Presented) The method according to claim 20,
- wherein the cryptographically transforming step includes using a relationship of the form $C \equiv M^e \pmod{n}$,
- wherein the exponent d is established based on the at least three distinct random prime numbers, p_1 , p_2 ,... p_k , using a relationship of the form $d \equiv e^{-1} \pmod{(p_1-1)\cdot(p_2-1)\cdots(p_k-1)}$, and
- wherein the cryptographically processed message is deciphered using a relationship of the form $M \equiv C^d \pmod{n}$.

- 22. (Previously Presented) A method for communicating a message cryptographically processed with RSA public key encryption, comprising the steps of:
- receiving from a sender a cryptographically processed message, in the form of a number C, which is decipherable by the recipient based on a number n, an exponent d, and the number C; and

deciphering the cryptographically processed message,

- wherein a number M represents a plaintext form of the message, wherein the number

 C represents a cryptographically encoded form of the message and is a function of the number M,
- the number n that is a composite number equaling the product of at least three distinct random prime numbers, wherein 0 < M < n-1, and
- an exponent e that is a number relatively prime to a lowest common multiplier of the at least three distinct random prime numbers,
- wherein the number n and exponent e are associated with the recipient to which the message is intended, and
- wherein the exponent d is a function of the exponent e and the at least three distinct random prime numbers;

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the at least three distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

- 23. (Previously Presented) The method according to claim 22,
 wherein the number C is formed using a relationship of the form C≡M^e (mod n),
 wherein the exponent d is established based on the at lest three distinct random prime
 numbers, p₁, p₂, ... p_k, using a relationship of the form d ≡ e⁻¹ (mod((p₁-1)·(p₂-1)···(p_k1))),
 and wherein the number M is obtained using a relationship of the form M≡C^d (mod n).
- 24. (Previously Presented) The method according to claim 21, wherein p and q are a pair of prime numbers the product of which equals n,

wherein the deciphering the number C to derive the number M is divided into subtasks, one subtask for each of the k distinct random prime numbers,

wherein the k distinct random prime numbers are each smaller than p and q,

whereby for a given length of n it takes fewer computational cycles to perform the deciphering relative to the number of computational cycles for performing such deciphering if the pair of prime numbers p and q were instead.

25. (Previously Presented) The method according to claim 22,

wherein p and q are a pair of prime numbers the product of which equals n,

wherein the deciphering the number C to derive the number M is divided into subtasks, one subtask for each of the k distinct random prime numbers,

wherein k distinct random prime numbers are each smaller than p and q,

whereby for a give length of n it takes fewer computational cycles to perform the deciphering relative to the number of computational cycles for performing such deciphering if the pair of prime numbers p and q were used instead.

26. (Previously Presented) The method according to claim 14,

wherein p and q are a pair of prime numbers the product of which equals n,

wherein the deciphering step is divided into sub-steps, one sub-step for each of the k distinct random prime numbers,

wherein the k distinct random prime numbers are each smaller that p and q,

whereby for a given length of n it takes fewer computational cycles to perform the deciphering step relative to the number of computational cycles for performing such deciphering step if the pair of prime numbers p and q were used instead.

27. (Previously Presented) The method according to claim 16,

wherein p and q are a pair of prime numbers the product of which equals n,

wherein the decoding step is divided into sub-steps, one sub-step for each of the k distinct random prime numbers,

wherein the k distinct random prime numbers are each smaller than p and q,

whereby for a given length of n it takes fewer computational cycles to perform the decoding step relative to the number of computational cycles for performing such decoding step if the pair of prime numbers p and q were used instead.

28. (Previously Presented) The method according to claim 18, wherein p and q are a pair of prime numbers the product of which equals n, wherein the encoding step is divided into sub-steps, one sub-step for each of the k distinct

random prime numbers,

- wherein the k distinct random prime numbers are each smaller than p and q, whereby for a given length of n it takes fewer computational cycles to perform the encoding step relative to the number of computational cycles for performing such encoding step if the pair of prime numbers p and q were used instead.
- 29. (Previously Presented) The method according to claim 14, wherein a message cryptographically processed by the sender with two-prime RSA public key encryption characterized by n being equal to a composite number computed as the product of 2 prime numbers p and q, is decipherable with multi-prime (k>2) RSA public key encryption characterized by the composite number n being computed as the product of the k distinct random prime numbers, $p_1, p_2, \dots p_k$.
- 30. (Previously Presented) The method according to claim 9, wherein the signed message word signal M_{1s} , formed from the digital message word signal M_1 being cryptographically processed at the first terminal with multi-prime (k>2) RSA public key encryption which is characterized by the composite number n being computed as the product of the k distinct random prime numbers, p_1 , p_2 , ... p_k , is decipherable at the second terminal with two-prime RSA public key encryption characterized by n being equal to a composite number computed as the product of 2 prime numbers p and q.
- 31. (Previously Presented) The method according to claim 16, wherein a message cryptographically processed by the sender with two-prime RSA public key encryption characterized by n being equal to a composite number computed as the product of 2 prime numbers p and q, is decipherable by the decoding with multi-prime (k>2) RSA public key encryption characterized by the composite number n being computed as the product of the k distinct random prime numbers, $p_1, p_2, \dots p_k$.

- 32. (Previously Presented) The method according to claim 18, wherein the signed message M_s , formed from the plaintext message data M being cryptographically processed at the sender with multi-prime (k>2) RSA public key encryption which is characterized by the composite number n being computed as the product of the k distinct random prime numbers, $p_1, p_2, \dots p_k$, is decipherable by the decoding at the recipient with two-prime RSA public key encryption characterized by n being equal to a composite number computed as the product of 2 prime numbers p and q.
- 33. (Previously Presented) The method according to claim 20, wherein a message cryptographically processed by the sender with two-prime RSA public key encryption characterized by n being equal to at composite number computed as the product of 2 prime numbers p and q, is decipherable at the recipient with multi-prime RSA public key encryption characterized by the composite number n being computed as the product of the at least three distinct random prime numbers.
- 34. (Previously Presented) The method according to claim 22, wherein a message cryptographically processed by the sender with two-prime RSA public key encryption characterized by n being equal to a composite number computed as the product of 2 prime numbers p and q, is decipherable at the recipient with multi-prime RSA public key encryption characterized by the composite number n being computed as the product of the at least three distinct random prime numbers.
- 35. (Previously Presented) A cryptography method for local storage of data by a private key owner,

comprising the steps of:

selecting a public key portion e;

- developing k distinct random prime numbers, p_1 , p_2 , ... p_k , where $k \ge 3$, and checking that each of the k distinct random prime numbers minus 1, p_1 -1, p_2 -1, ... p_k -1, is relatively prime to the public key portion e;
- establishing a private key portion d by a relationship to the public key portion e in the form of $\underline{d} \equiv e^{-1} \pmod{(p_1-1)\cdot(p_2-1)\cdots(p_k-1)}$;
- computing a composite number, n, as a product of the k distinct random prime numbers that are factors of n, where only the private key owner knows the factors of n; and

encoding plaintext data M to ciphertext data C for the local storage, using a

relationship of the form C≡M^e (mod n), wherein 0≤M≤n-1, whereby the

ciphertext data C is decipherable only by the private key owner having

available to it the factors of n;

wherein p and q are a pair of prime numbers that product of which equals n, and
wherein developing the k distinct random prime numbers and computing the composite
number n is performed, including for n that is more than 600 digits long, in less time
than it takes to develop the pair of prime numbers p and q and compute that n.

- 36. (Previously Presented) The cryptography method in accordance with claim 35, further comprising the step of:
- decoding the ciphertext data C from the local storage to the plaintext data M using a relationship of the form $M \equiv C^d \pmod{n}$.
- 37. (Previously Presented) A cryptographic communications system, comprising: a plurality of stations;

a communications medium; and

a host system adapted to communicate with the plurality of stations via the communications medium sending a receiving messages cryptographically processed with an RSA public key encryption, the host system including

at least one cryptosystem configured for

developing k distinct random prime numbers, $p_1, p_2, ..., p_k$, where $k \ge 3$,

- checking that each of the k distinct random prime numbers minus 1, p₁-1, p₂-1, ... p_k
 1, is relatively prime to a public key portion e that is associated with the host system,
- computing a composite number, n, as a product of the k distinct random prime numbers,
- establishing a private key portion d by a relationship of the public key portion e in the form of $d \equiv e^{-1} \pmod{(p_1-1)\cdot(p_2-1)\cdots(p_k-1)}$,
- in response to an encoding request from the host system, encoding a plaintext message data M producing therefrom a ciphertext message data C to be

communicated via the host system, the encoding using a relationship of the form $C \equiv M^e \pmod{n}$, where $0 \leq M \leq n-1$,

in response to a decoding request from the host system, decoding a ciphertext

message data C' communicated via the host producing therefrom a plaintext

message data M' using a relationship of the form M'≡C'^d (mod n);

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

38. (Previously Presented) A system for communications of a message cryptographically processed with RSA public key encryption, comprising:

a bus; and

a cryptosystem communicatively coupled to and receiving from the bus encoding and decoding requests, the cryptosystem being configured for

providing a public key portion e,

developing k distinct random prime numbers, $p_1, p_2, \dots p_k$, where $k \ge 3$, checking that each of the k distinct random prime numbers minus 1, p_1 -1, p_2 -1, ... p_k -1, is relatively prime to the public key portion e,

computing a composite number, n, as a product of the k distinct random prime numbers,

establishing a private key portion d by a relationship to the public key portion e in the form of $d \equiv e^{-1} \pmod{(p_1-1)\cdot(p_2-1)\cdots(p_k-1)}$,

in response to an encoding request from the bus, encoding a plaintext form of a first message M to produce C, a ciphertext form of the first message, using a relationship of the form $C \equiv M^e \pmod{n}$, where $0 \le M \le n-1$, and

in response to an decoding request from the host system, decoding C', a ciphertext

form of a second message, to produce M', a plaintext form of the second

message, using a relationship of the form M'\(\existsime C'_d\) (mod n), the first and second

messages being distinct or one and the same;

wherein p and q are a pair of prime numbers that product of which equals n, and

wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

- 39. (Previously Presented) The system of claim 37, wherein the at least one cryptosystem includes
- a plurality of exponentiators configured to operate in parallel in developing respective subtask values corresponding to the message.
- 40. (Previously Presented) The system of claim 37, wherein the at least one cryptosystem includes

a processor,

a data-address bus,

a memory coupled to the processor via the data-address bus,

- a data encryption standard (DES) unit coupled the memory and the processor via the data-address bus,
- a plurality of exponentiator elements coupled to the processor via the DES unit, the

 plurality of exponentiator elements being configured to operate in parallel in

 developing respective subtask values corresponding to the message.
- 41. (Previously Presented) The system of claim 40, wherein the memory and each of the plurality of exponeniator elements has its own DES unit that cryptographically processes message data received/returned from/to the processor.
- 42. (Previously Presented) The system of claim 40, wherein the memory is partitioned into address spaces addressable by the processor, including secure, insecure and exponentiator

elements address spaces, and wherein the DES unit is configured to recognize the secure and exponentiator elements address spaces and to automatically encode message data therefrom before it is provided to the exponentiator elements, the DES unit being bypassed when the processor is accessing the insecure memory address spaces, the DES unit being further configured to decode encoded message data received from the memory before it is provided to the processor.

- 43. (Previously Presented) The system of claim 40, wherein the at least one cryptosystem meets FIPS (Federal Information Processing Standard) 140-1 level 3.
- 44. (Previously Presented) The system of claim 40, wherein the processor maintains in the memory the public key portion e and the composite number n with its factors $p_1, p_2, \dots p_k$.
- 45. (Previously Presented) A system for communications of a message cryptographically processed with RSA public key encryption, comprising:

a bus; and

a cryptosystem receiving from the system via the bus encoding and decoding requests, the cryptosystem including

a plurality of exponentiator elements configured to develop subtask values,

a memory, and

a processor configured for

receiving the encoding and decoding requests, each encoding request providing a plaintext message M to be encoded,

obtaining a public key that includes an exponent e and a modulus n, a representation of the modulus n existing in the memory in the form of its k distinct random prime number factors $p_1, p_2, \ldots p_k$, wherein $k \ge 3$, constructing subtasks, one subtask for each of the k factors, to be executed by the exponentiator elements for producing respective ones of the subtask values, $C_1, C_2, \ldots C_k$, and

forming a ciphertext message C from the subtask values $C_1, C_2, \dots C_k$, wherein the ciphertext message C is decipherable using a private key that includes the modulus n and an exponent d which is a function of e;

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

46. (Previously Presented) The system of claim 45, wherein each one of the subtasks C_1 , C_2 , ... C_k is developed using a relationship of the form $C_i \equiv M_i^{e_i} \pmod{p_i}$, where $M_i \equiv \pmod{p_i}$, and $e_i \equiv \pmod{p_i-1}$, and where i=1, 2, ... k.

47. (Previously Presented) A system for communications of a message cryptographically processed with RSA public key encryption, comprising:

a bus; and

a cryptosystem receving from the system via the bus encoding and decoding requests, the cryptosystem including

a plurality of exponentiator elements configured to develop subtask values, a memory, and

a processor configured for

receiving the encoding and decoding requests, each encoding/decoding request provided with a plaintext/ciphertext message M/C to be encoded/decoded and with or without a public/private key that includes an exponent e/d and a modulus n representation of which exists in the memory in the form of its k distinct random prime number p_1, p_2, \ldots p_k , where $k \ge 3$,

obtaining the public/private key from the memory if the encoding/decoding request is provided without the public/private key.

constructing subtasks to be executed by the exponentiator elements for producing respective ones of the subtask values, M_1 , M_2 , ... M_k/C_1 , C_2 , ... C_k , and

forming the ciphertext/plaintext message C/M from the subtask values $C_1, C_2, ...$

 $\underline{C_k/M_1, M_2, \dots M_k}$;

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

48. (Previously Presented) The system of claim 47 wherein when produced each one of the subtasks $C_1, C_2, \ldots C_k$ is developed using a relationship of the form $C_i \equiv M_i^{e_i} \pmod{p_i}$, where $C_1 \equiv C \pmod{p_i}$, and $e_i \equiv e \pmod{p_i-1}$, and where $i=1, 2, \ldots k$.

- 49. (Previously Presented) The system of claim 47 wherein when produced each one of the subtasks $M_1, M_2, ... M_k$ is developed using a relationship of the form $M_i \equiv C_i^{d_i} \pmod{p_i}$, where $M_i \equiv M \pmod{p_i}$, and $d_i \equiv d \pmod{p_i-1}$, and where i=1, 2, ... k.
- 50. (Previously Presented) The system of claim 49, wherein the private key exponent d relates to the public key exponent e vai $d \equiv e^{-1} (\text{mod}((p_1 1) \cdot (p_2 1) \cdots (p_k 1)))$.
- 51. (Previously Presented) A system for communications of a message cryptographically processed with RSA public key encryption, comprising:

means for selecting a public key portion e;

- means for developing k distinct random prime number $p_1, p_2, \dots p_k$, where $k \ge 3$, and for checking that each of the k distinct random prime numbers minus $1, p_1-1, p_2-1, \dots p_k-1$, is relatively prime to the public key portion e;
- means for establishing a private key portion of d by a relationship to the public key portion e
 in the form of $d \equiv e^{-1} (\text{mod}((p_1 1) \cdot (p_2 1) \cdots (p_k 1)));$
- means for computing a composite number, n, as a product of the k distinct random prime numbers;

means for receiving a ciphertext message data C; and

means for decoding the ciphertext message data C to a plaintext message data M using a relationship of the form $M \equiv C^d \pmod{n}$;

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

- 52. (Previously Presented) The system according to claim 51, further comprising:

 means for encoding the plaintext message data M to the ciphertext message data C, using a

 relationship of the form $C \equiv M^e \pmod{n}$, where $0 \le M \le n-1$.
- 53. (Currently Amended) A system for communications of a message cryptographically processed with RSA public key encryption, comprising:

means for selecting a public key portion e;

means for developing k distinct random prime number $p_1, p_2, \dots p_k$, where $k \ge 3$, and for checking that each of the k distinct random prime numbers minus $1, p_1-1, p_2-1, \dots p_k-1$, is relatively prime to the public key portion e;

means for establishing a private key portion d by a relationship to the public key portion e of

the form $d \equiv e^{-1} (\text{mod}((p_1 - 1) \cdot (p_2 - 1) \cdots (p_k - 1)));$

means for computing a composite number, n, as a product of the k distinct random prime numbers; and

means for encoding a plaintext message data M with the private key portion d to produce a signed message M, using a relationship of the form $M_s \equiv M^d$ (mod n), where $0 \le M \le n-1$, the signed message M_s being decipherable using the public key portion e;

wherein p and q are a pair of prime numbers that product of which equals n, and wherein developing the k distinct random prime numbers and computing the composite number n is performed, including for n that is more than 600 digits long, in less time than it takes to develop the pair of prime numbers p and q and compute that n.

54. (Previously Presented) The system of claim 53 further comprising the step of:

means for decoding the signed message M_s with the public key portion e to produce the plaintext message data M using a relationship of the form $M \equiv M_s^e \pmod{n}$.

- 55. (Previously Presented) The system of claim 52, wherein the system can communicate the cryptographically processed message to another system that encodes/decodes data with RSA public key encryption using a modulus value equal to n independent of the k distinct prime numbers.
- 56. (Previously Presented) The system of claim 53, wherein the system can communicate the cryptographically processed message to another system that encodes/decodes data with RSA public key encryption using a modulus value equal to *n* independent of the *k* distinct prime numbers.